

Amendments to Claims:

This listing of claims replaces all prior versions and listings of claims in the application.

Listing of Claims:

Claim 1 (Currently Amended): An information processing apparatus operable from
a remote user comprising:

a communication unit which provides a function to interface with a network;

a connection request unit which generates a request to establish a connection with the
network;

an address holder which holds a logical address allotted when the connection
is established;

an address reporting unit which sends the allotted logical address to a network
node of the remote user; and

a server function unit which provides a predetermined service, when ~~[[a]]~~ the network
node of the remote user accesses the apparatus using the ~~sent~~ allotted logical address, to the
node as a client.

Claim 2 (Original): The apparatus of claim 1 further comprising a monitor unit which
detects a trigger signal transmitted by a remote node in compliance with a communication
protocol which does not require connection to the network, wherein the connection request unit
generates the request upon detecting the signal.

Claim 3 (Original): The apparatus of claim 1 further comprising:

a second communication unit which communicates with an external appliance which is under the control of the apparatus; and

an appliance controller which controls the external appliance via the second communication unit;

wherein the server function unit, as the predetermined service, receives an instruction for the control of the external appliance from the user node and transmits the instruction to the appliance controller and the appliance controller converts the instruction to a control command of the external appliance and sends the command to the appliance via the second communication unit.

Claim 4 (Original): The apparatus of the claim 1 further comprising a second monitor unit which generates a trigger signal when status of the external appliance reported via the second communication unit satisfies a predetermined condition, wherein the connection request unit generates the request upon detecting the signal generated by the second monitor unit.

Claim 5 (Original): The apparatus of claim 1 further comprising a third monitor unit which generates a trigger signal when information from a sensor sensing ambient environment satisfies a predetermined condition, wherein the connection request unit generates the request upon detecting the signal generated by the third monitor unit.

Claim 6 (Original): The apparatus of claim 1 further comprising a disconnection request unit which disconnects from the network when access from the logical address has been suspended for a predetermined period.

Claim 7 (Original): The apparatus of claim 2 further comprising an authentication unit which determines whether the remote node that issued the trigger signal is a user node managed by the apparatus.

Claim 8 (Original): The apparatus of claim 2 further comprising:
a second communication unit which communicates with an external appliance which is under the control of the apparatus; and
an appliance controller which controls the external appliance via the second communication unit;
wherein the server functional unit, as the predetermined service, acquires an instruction for the control of the external appliance from the user node and transmits the instruction to the appliance controller and
the appliance controller converts the instruction to a control command from the external appliance and sends the command to the appliance via the second communication unit.

Claim 9 (Original): The apparatus of the claim 3 further comprising a second monitor unit which generates a trigger signal when the status of the external appliance reported via the second communication unit satisfies a predetermined condition, wherein the connection request unit generates the request upon detecting the signal generated by the second monitor unit.

Claim 10 (Original): The apparatus of claim 4 further comprising a third monitor unit which generates a trigger signal when information from a sensor sensing ambient environment satisfies a predetermined condition, wherein the connection request unit generates the request upon detecting the signal generated by the third monitor unit.

Claim 11 (Original): The apparatus of claim 5 further comprising a disconnection request unit which disconnects from the network when access from the logical address has been suspended for a predetermined period.

Claim 12 (Currently Amended): An information processing method operable from a remote user comprising:

- waiting in a stand-by mode in an offline state as an initial state;
- establishing connection with a network upon detecting a predetermined trigger signal;
- receiving and holding a logical address allotted when the connection is established;
- sending the ~~held~~ allotted logical address to a network node of the remote user; and
- providing a predetermined service, when a network node of the remote user connects to the ~~sent~~ allotted logical address, to the node as a client.

Claim 13 (Currently Amended): An information processing apparatus operable from a remote user comprising:

- a communication means for providing a function to interface with a network;
- a connection request means for generating a request to establish a connection with the network;

an address holding means for holding a logical address allotted when the connection is established;

an address reporting means which sends the allotted logical address to a network node of the remote user; and

a server function means for providing a predetermined service, when ~~[[a]]~~ the network node of the remote user accesses the apparatus using the ~~sent~~ allotted logical address, to the node as a client.

Claim 14 (Currently Amended): An information processing method operable from a remote user comprising the steps of:

waiting in a stand-by mode in an offline state as an initial state;
establishing connection with a network upon detecting a predetermined trigger signal;
receiving and holding a logical address allotted when the connection is established;
sending the ~~held~~ allotted logical address to a network node of the remote user; and
providing a predetermined service, when ~~[[a]]~~ the network node of the remote user connects to the ~~sent~~ allotted logical address, to the node as a client.

Claim 15 (Original): The apparatus of claim 1, wherein said network is the Internet, wherein the connection request unit relies on PPP and wherein the logical address is an IP address.

Claim 16 (Original): The method of claim 12, wherein said network is the Internet, wherein the connection relies on PPP and wherein the logical address is an IP address.

Response under 37 C.F.R. §1.111

Attorney Docket No. 021380

Serial No. 09/880,731

Claim 17 (New): The apparatus of claim 2, wherein the allotted logical address is sent to the network node of the remote user by an e-mail.